

ENDOEYE 3D 10 MM

Video Telescope



ENDOYE 3D 10 MM

3D-Image Rotation without Loss of Horizon

- Change the view direction while maintaining horizontal orientation of images, enabling a continuous critical view in 3D

Chip-on-the-Tip Technology

- Bright, clear, and natural 3D depth perception
- Focus-free handling; no manual focusing required

Autoclave Compatibility

- Reduced costs compared with other sterilization methods

Full Control During Surgery

- Three programmable remote control buttons

Plug and Play

- Simple to set up and easy to use

Ordering Information							
Order Number	Outer Diameter	Direction of View	Field of View	Working Length	Max. Insertion Portion Width	Cable Length	Weight
WA50080A	10 mm	0°	67°	330 mm	10.07 mm	2780 mm	290g
WA50082A	10 mm	30°	67°	335 mm	10.20 mm	2780 mm	290g

Specifications			
Reprocessing Methods	Autoclavable, ETO, STERRAD, washer-disinfector		
Ambient Conditions	Operating conditions	Ambient temperature	10 to 35°C (50 to 95°F)
		Relative humidity	30 to 85%
	Storage conditions	Temperature	10 to 40°C (50 to 104°F)
		Relative humidity	30 to 75%
	Transport conditions	Temperature	–47 to 70°C (–53 to 158°F)
		Relative humidity	10 to 95%
Classification of ME Equipment and ME Systems	Protection against electric shock: Classification of applied parts		Type BF
	Protection against harmful ingress of water or particulate matter		IPX7



Specifications, design, and accessories are subject to change without any notice or obligation on the part of the manufacturer.